

Standard CNC with enhanced basic performance and productivity

FANUC

Series 0i-MODEL F Plus



FANUC's New Standard CNC

FANUC Series Oi-MODEL F Plus

More powerful and easier to use

- Improved visibility and operability with renewal design of screen
- Equipped with **iHMI** for consistent support at shop floor
- Equipped with FANUC's latest CNC and Servo technologies
- Customizable functions for characteristic screens and operation as standard
- Extended memory capacity for storing large sized program
- Easy robots connection and control

Machining Performance

- Improved productivity through reduced cycle times
 - ▶ Fast Cycle-time Technology
- Achieves high-quality machining
 - ▶ Fine Surface Technology

Two-product line-up covering different purposes

CNC for Machining Center

FANUC Series Oi-MF Plus

- 1-path system total controllable axes: up to 18
- 2-path system total controllable axes: up to 18
- Simultaneous controlled axes : up to 4 axes

CNC for Lathe

FANUC Series Oi-TF Plus

- 1-path system total controllable axes: up to 18
- 2-path system total controllable axes: up to 18
- Simultaneous controlled axes : up to 4 axes

(Total controllable axes: total of feed axes, spindles and peripheral axes)



Maximizing Uptime

- Prevent sudden machine downtime with preventive maintenance
 - ▶ Extensive failure prediction functions
- Reduce recovery time by easily pinpointing faulty parts
 - ▶ Diagnosis/maintenance functions


Ease of Use

- Consistent support at shop floor
 - ▶ **FANUC iHMI**
- Original screen for ease of use
 - ▶ Comes standard with customizable functions
- IoT integration
 - ▶ Extensive compatibility with field networks

System configuration

CNC control unit (LCD mounted type/stand-alone type)

Line-up of displays that are compatible with the various types of machine tools, from compact to large and standard to high-spec, such as the FANUC *i*PC, PANEL *i*H compatible with *i*HMI and the compact 10.4" LCD/MDI unit.



Handheld unit

Equipped with an emergency stop button and a manual pulse generator, this handy unit line-up achieves safe manual operation of machine tools.



I/O Unit

Wide range of I/O units compatible with various installation locations and I/O devices.

Optimized for operator's panels with its thin and space-saving design

Standard operator's panel with key input duplication

Handles the output/input of safety signals

Compatible with original operator's panels



Safety Machine operator's panel



I/O module for operator's panel supporting safety function




I/O module for operator's panel

Optimized for control cabinets multi-point output/input type

Small size I/O unit with improved expandability, workability and maintainability

Excellent performance multi-point out



FANUC Slice I/O



I/O unit for magnetics

with high scalability and extensive modules such as the analog/digital output/input module


cost with put/input

Compact and with reduced wiring



I/O unit for connector panel

Effective for thermal displacement compensation with multi-point temperature sensor input



Temperature sensor input unit

Optimized for reduced wiring by enabling distributed setup


Can be positioned near sensors scattered inside and outside the machine cabinet

IP67 type



I/O Unit-MODEL B

Ethernet



Servo motor

Line-up to meet the various needs of machine tools and contribute to the performance improvement of feed axes



SERVO MOTOR *alpha-i-D* series



DD MOTOR *DiS-B* series



LINEAR MOTOR *LiS-B* series

Spindle motor

Line-up to meet the various needs of machine tools and contribute to the performance improvement of spindles



SPINDLE MOTOR *alpha-i-D* series



BUILT-IN SPINDLE MOTOR *Bi-B* series

Servo amplifier


Line-up to be flexibly available for a variety of machine tools and contribute to the downsizing of cabinets



SERVO AMPLIFIER *alpha-i-D* series

Fast Cycle-time Technology

Fast Cycle Time Technology refers to CNC and servo technologies that achieve reduced cycle times. It reduces cycle times of machining programs through methods such as accelerating and decelerating depending on the operational state, making the best use of spindle performance, and reducing the sequence processing time for external signals.




Fast Cycle-time setting

Easily reduce cycle times

The Fast Cycle-time setting compares the currently set parameter setting to the FANUC default setting, allowing you to easily use the setting that most effectively reduces cycle time.




Reduced cycle time example: Workpiece for evaluation



Before application 4 minutes 47 seconds → After application 4 minutes 4 seconds
Approx. 15% reduction


Smart Servo Control

Smart Servo Control is a group of functions to optimize control in real time according to the change of machine conditions such as load and temperature. These functions contribute to high-speed, high-precision and high-quality machining as the control technology supporting Fast Cycle-time Technology and Fine Surface Technology.




Fine Surface Technology

Fine Surface Technology is a collective term for CNC and servo technologies that achieve fine surface machining. This technology allows for the interpolation of high precision machining program output from CAD/CAM, high-speed execution of small segment programs, the generation of a smooth tool path and accurate command follow-up. These tasks more efficiently by taking digital technology.



Fine Surface settings


Standard setting values are provided based on machining conditions (roughing, semi-finishing, or finishing), and slide bars can be intuitively used to set and adjust high-speed, high-precision machining parameters based on the machine. Machining under optimal conditions can be achieved by selecting machining processes during the machining itself using a machining program or screen operations.



Smooth Tolerance+ Control


Smoothing continuous small blocks to realize fine surface machining

The machining path specified in continuous small blocks, like the one for mold machining, is smoothed out within the specified allowance error tolerance. The smooth machining path reduces mechanical shock and improves the quality of the machined surface.



Servo Learning Oscillation

Servo learning oscillation that applies servo learning control also accurately tracks oscillation commands with a high frequency, thereby achieving dependable chip shredding. It can be applied to turning, drilling and threading.




Excellent control function

Machining Performance

Smooth TCP

Simultaneous 4-axis machining including the rotation axis is available with the program that specified tool center point path.



Tool center point path follows specified path with high accuracy interpolation. This function can achieve smooth machining of complicated shapes including undercuts like an impeller that cannot be machined with 3 axes. Tool offset and kinematic conversion applied to a rotary-axis are executed by CNC. So that, a machine configuration is not needed to consider on the CAM side, and improves affinity with CAD/CAM.



Excellent Operability

Ease of Use

Large Capacity Program Memory

You can use large capacity program memory that can store large sized programs. Programs stored in program memory can be operated by memory operation. Also, edit can be done.

Extended Program Memory (CF card)

Using a CF card installed in the memory card slot of the display unit as program memory.

- Maximum capacity is about 4GB.
- Recommended if you use standard display unit.
- Having excellent cost performance.
- Total number of programs and folders that you can register has expanded to 1000.

Extended Program Memory (PC)


Using HDD/SSD of PC like PANEL *iH/iH Pro* as program memory.

- Maximum capacity is 40GB.
- Recommended if you use display unit with PC function like PANEL *iH/iH Pro*.
- Having excellent cost performance.
- High speed GOTO jump and high speed search can be done.

Utilization of USB Memory

Load & Go function

- Program on USB memory can be operated easily by Load & Go function.
- Copy from USB memory & Selection to main program is completed with one touch.



Consistent Support at Shop Floor

Ease of Use

FANUC *i*HMI

FANUC *i*HMI supports all jobs at the shop floor consistently, exceeding a limit of conventional CNC operation. For the flow of "planning," "machining," and "improvement," process, various functions such as tool data registration, machining time prediction, programming, and post-machining inspection have been provided. Any of them can be easily operated by intuitive operability. In addition, at the center of each function is the home screen, which can be displayed from any screen with a dedicated key, so there is a sense of security that you can return at any time.




HOME screen

CNC operation

The CNC operation screen has been consolidated into three screens: "programming," "setup," and "machining," which reduces screen switching operations and greatly improves operability. In the CNC operation screen, machining programs can be easily recognized and easily created, such as color-coded display for each command and comment input function for tool information.

- G-code Guidance enables easy programming with machining selection and input screen even if complex command. It reduces program creation time and errors.
- Machining program preview detects programming errors before machining. It reduces working time and costs.
- The help, troubleshooting, and other functions are available to solve problems at a time if you have difficulty.




CNC operation screen

Tool manager

- Tool data of each application of FANUC *i*HMI can be centrally managed and all the tool data can be referred here.
- By reading the catalog data provided by tool makers, such as mold model number, dimensions, and machining conditions of the tool, the time to enter the tool data can be reduced.

Maintenance manager

- Prevent check leak of maintenance parts by collective management of maintenance parts for machines and for CNC, amp, and motor.
- Prevent errors by working maintenance with checking the maintenance manual.




G-code Guidance

SERVO VIEWER

- SERVO VIEWER offers the waveform display of the machine operation such as position of feed axes and torque of spindle.
- PMC signals and sequence numbers can be observed simultaneously.
- Useful for reducing cycle time and improving cutting condition, without any additional equipment.

Manual viewer

- Not only CNC manuals, but also machine manuals and work procedure manuals can be registered.
- You can check it in front of the machine without having to look for a paper manual or return to your office computer.



Machining program preview

Many Customizable Functions

Ease of Use

Customizable functions are available, which allow machine tool builders to customize their own machine tools

Customizing operation screens


FANUC PICTURE

This tool enables you to create a machine operation screen simply by pasting screen components such as buttons and lamps on the PC.

- The screen creation tool is FANUC's proprietary easy-to-use user interface that is optimized for creating screens for CNCs.
- Screens that are created can be displayed and operated on various CNC models.
- Complicated controls such as network communication and file control can be easily implemented by using general-purpose scripts.

In addition, in the PANELi series display device, it is possible to create screens that leverage the performance of display devices.

- You can display the font for each language of any desired size.
- You can display buttons, lamps, and high precision images in full color.



C Language Executor

Machine tool builders can create their own operation screens, which enables unique CNC display and operation.

- C language is used for programming.
- Multi window display enables creation of pop-up menus.
- Operation screens using the touch panel can be created.
- In addition to standard ANSI functions, many functions are available for CNCs and PMCs.
- High-level tasks to which high execution priority is assigned can monitor signal and position information.




Implementing original sequence control based on PMC

FANUC LADDER-III

For machine customization, a machine tool builder's own sequence control can be incorporated into the built-in PMC. A PMC sequence program can be created on a personal computer by using FANUC LADDER-III, a very easy-to-use programming tool with many useful functions.

- A program can be created with ladder and function block.
- A program can be coded using signal names instead of signal addresses.
- Online monitoring and editing can be performed by connecting a personal computer with the CNC via Ethernet.
- Including PMC Function Library which enables you to integrate functions such as PMC axis control easily.



Pursuing Ease of Use

Ease of Use

Set-up Guidance Function

Measurement is achieved by touching the tool to the work manually. And the measurement value can be set to the work coordinate system. As a result, the arrangements time can be greatly reduced.

- Single surface measurement
- Outside diameter measurement
- Inside diameter measurement
- Outside width measurement
- Inside width measurement
- Measurement of corner outside
- Measurement of corner inside
- Angled work measurement




Support for adding sensors and peripheral devices

Multi C Language Executor

New custom screens can be easily added without changing the custom screens implemented in the machine (created with FANUC PICTURE or C language Executor).

Ladder Dividing Management Function

Ladders for controlling sensor or peripheral equipment can be added without changing the ladder for machinery control already implemented in the machine.



Easy Robots Connection and Control

Ease of Use


Integration of Robots to Machine Tools

This function allows you to easily connect a FANUC robot to a machine tool. Machine users with no experience using robots will be able to use robots easily.

Robot G-CODE

Robots can be operated with the feel of a machine tool.


- Utilize robots as part of machine tools with CNC programs (G code commands)
- By using familiar machine tool handles, robots can be positioned and taught easily from CNC screen



Robot ON-SITE

Robots can be installed on existing machines without changing machine tool system modification.

- Easy connection of CNC and robot via Ethernet cable without additional hardware
- Robot operation by using macro variables without ladder change



Robot Auto Path Generation

This function makes it possible to automatically generate a robot path that does not interfere with PC tools.

- Automatically generate path that does not interfere with the machine tool just by specifying the start point and end point
- The generated path can be confirmed by simulation, reducing man-hours for teaching robot.




Network Support Functions

Ease of Use

Advancing the IoT adaptability of CNC machine tools with extensive network functions

Ethernet / Industrial Ethernet / Field Network

You can use Embedded Ethernet provided as standard and Fast Ethernet with a communication dedicated processor for NC program transfer and remote maintenance. Various types of Industrial Ethernet and Field Networks are supported to enable various types of peripheral devices to be connected for controlling peripheral devices such as waterproof I/O devices and collecting sensor information. Via a MULTI SENSOR I/O UNIT or other devices, information of impact, temperature, and other sensors can also be read.



Supported Industrial Ethernet/Field Networks


- FL-net
- EtherNet/IP (master/slave)
- PROFINET (master/slave)
- Modbus/TCP (slave)
- EtherCAT (master)
- CC-Link IE Field (slave)
- PROFIBUS-DP (master/slave)
- DeviceNet (master/slave)
- CC-Link (slave)

FANUC MT-LINK*i* (Operation Management software)

MT-LINK*i*

MT-LINK*i* is a software product that can collect, manage, and help visualize various information of machines connected via Ethernet. It helps visualize the machines in factories, and contributes to minimizing downtime.

- It can collect device information not only from machine tools equipped with FANUC CNCs, but also from FANUC robot controllers, OPC-compatible PLCs, and MTConnect-compatible machine tools.
- Information of existing devices that do not have Ethernet I/F can also be collected by using an Ethernet I/O converter.
- Many standard screens that display various pieces of information such as the operational states and operational results of machines are available.




Standard screen example)



Visualization of machine operation

By using MT-LINK*i* together with SERVO VIEWER, servo data and various status signals are collected, achieving the visualization of detailed machine operations.

- High-speed sampling (1ms) servo data is efficiently collected from multiple machine tools.
- Various schedule and trigger functions enable efficient analyses by collecting only required data at the right timing.



Powerful PMC

Ease of Use

High-Speed, Large Capacity, and Multi-path PMC

High-Speed and Large Capacity


The integrated PMC now achieves even higher speeds. Large-scale sequence controls can be processed at high speed using the powerful dedicated processor and the latest custom LSI.

- Program capacity Max. 100,000 steps (Total of all PMC paths)
- Internal relay (R) Max. 60,000 bytes
- Data table (D) Max. 60,000 bytes
- PMC paths Max. 3 paths (Max. 16 ladder programs)

Multi-path PMC

One PMC can execute up to three independent ladder programs, including loader control and peripheral equipment control.


- Ladder programs can easily be developed according to each user's machine configuration.
- Cost reductions are achieved by eliminating external PLCs or other devices for peripheral equipment control.



Function Block function


- This function enables repeated ladder circuit patterns to be arranged in function blocks and easily reused.
- The PMC function libraries attached to FANUC LADDER-III include functions ready for immediate embedding such as PMC axis and peripheral equipment control, and can be freely customized.

Reuse ladder circuits as function blocks



A full range of libraries are included in FANUC LADDER-III

- PMC axis control
- Operator's panel
- Spindle functions
- I/O devices
- CNC functions
- Others



Safety functions

Ease of Use

Improvement of the safety of machine tool and machining line

Dual Check Safety Function

This is a safety function integrated into the CNC that conforms to ISO 13849-1 PL d. Multiple processors perform dual monitoring of the actual positions, speed, and safety-related I/O of servo motors and spindle motors, securing a high level of safety by providing duplicated paths for cutting off power.

Network safety function

By combining this function with the Dual Check Safety function, safety functionality of the machining line is achieved.


- Safety function by FL-net
- EtherNet/IP Adapter Safety function
- PROFINET IO Device Safety function
- PROFINET IO Controller Safety function

Safe Torque Off (STO) function

This is a safety function integrated in servo amplifiers that conforms to IEC 61800-5-2. Motor power can be safely cut off by the duplicated cut-off path within the amplifier.

Dual Check Safety Function

- The machine can be operated safely while the protective door is open



Easy Maintenance


Maximizing Uptime

Functions for minimizing downtime

Contribution to Preventive Maintenance

Cooling Fan Warning Function

By monitoring a decrease in the rotational speed of each cooling fan motor of the CNC and the servo amplifier, signs of fan abnormalities can be detected. This function enables preventive maintenance. Fans are stored in a cartridge and can be replaced quite easily, so maintainability is enhanced.





Failure Part Detection

Trouble Diagnosis Function

Various failure detection functions provided to the I/O Link *i* and FSSB can detect interruptions in the power supply to the I/O modules or servo amplifier and identify disconnection locations of the communication cable. In addition to that, I/O Link *i* can detect the ground fault of each DO.


The trouble diagnosis function enables you to see diagnosis information helpful in determining the status when an alarm occurs on the CNC screen.

- Trouble diagnosis guidance screen
- Trouble diagnosis monitor screen
- Trouble diagnosis graph screen



Encoder Communication Check Circuit

This check circuit enables a quick recovery from encoder communication alarm by identifying which part such as encoder, feedback cable or servo amplifier has failed.




Reduction of Recovery Time

FANUC Slice I/O

Exchangeable of electronics housing without removing wires due to 3-Pieces Structure; "Front connector", "Electronics" and "Base".

In addition to that, following functions can easy detect failure module.

- LED indication for each signal state and unit status
- Enable voltage check of each I/O terminal
- Display nickname of each module on the front of module




Prevent Machine Damage at Power Failure

Machine Protection at Power Failure

Damage of machines and workpieces at power failure is prevented where a power supply is unstable or in a lightning-prone areas.

- **Gravity-axis drop prevention**
The holding brake of gravity axis are quickly activated by detecting power failure in the circuit incorporated into the amplifier.
- **Stop distance reduction*1)**
Feed axes are quickly stopped to avoid a crash in high-speed machine tools.
- **Retraction*2)**
The tool is retracted from the workpiece while keeping synchronization in gear cutting machines and others.



*1), *2) "Power Failure Backup Module (Hardware)" or "Power Failure Backup Function (Software)" shall be applied.

Digital Twin for FANUC CNC


Supporting productivity improvement for machine tool builders and machine users

Supports efficiency for machine tool design, processing and maintenance

FANUC Smart Digital Twin®

Consolidated FANUC CNC technology and Digital technology improves productivity. Part of operation that was available only on machine in the past can be done on PC.


- Improvement of machine utilization rate by not occupying the machine
- Shorten working time by high-speed simulation
- Contribution to energy saving by reducing work-pieces and tools for test cutting



FANUC CNC GUIDE 2

This is a core technology of digital twin for FANUC CNC and a software tool that enables verification of CNC functions on PC.


- Realization of more realistic simulation by using Servo Model which reflects characteristics of controlled axes and the maximum 20 times faster simulation than actual machining
- Simulation of the machine motion and the machined surface working with CNC Reflection Studio and Surface Estimation
- By connecting the MOP simulator that integrates the MDI and the operation panel, it is possible to train CNC operation with the same operation feeling as an actual machine tool



FANUC CNC Reflection Studio

It is a software tool that visualizes machine movement according to machining program execution.


- Safe and high-speed machine collision check can be done in digital space
- G-code analysis/interpolation processing are equivalent to actual CNC by cooperation with CNC GUIDE 2



FANUC SERVO VIEWER Surface Estimation

It is a software tool that estimates machining surface accurately using position data of CNC GUIDE 2 machining program execution or dry running of actual machine.


- Surface quality issue like streaks can be checked digitally before actual cutting
- Trouble shooting becomes easier by understanding relation between surface and machining program or used tools



FANUC Tool Path Optimizer

It is a software tool that compensates the tool path using the machining shape (CAD data).

- Machining program is optimized for FANUC CNC regardless of type of CAM software that generated the machining program
- The quality of the machined surface is improved by reducing scratches and steps on the machined surface caused by the tool path




Support of Efficient Servo Tuning for High-Speed and High-Precision Machining

FANUC SERVO GUIDE Plus

Integrated tuning tool for Servo and Spindle

SERVO GUIDE Plus helps to improve machining performance through the various waveform analysis and the optimization of servo/spindle parameters according to machine characteristics.

- All in one package for servo tuning including data measurement, parameter management and test program preparation
- Various views of waveform helps easy analysis of machine condition
- AI Servo Tuning is an auto-tuning algorithm with artificial intelligence. It can optimize parameters easily and in a short time.
- 3-D View Function (option) visualizes the tool path and path error and helps trouble shooting of 5-axis machining



Service & Support

Excellent Maintenance Services

FANUC service team delivers customer trust and confidence based on direction of service “Maximizing Uptime”, “Global Service” and “Lifetime maintenance”.

Service First

Conforming to the spirit of “Service First”, FANUC provides lifetime maintenance to its products for as long as they are used by customers, through more than 270 service locations supporting more than 100 countries and regions throughout the world.

Maximizing Uptime



FANUC ACADEMY

FANUC ACADEMY operates versatile training courses to develop skilled engineers effectively in several days.



FANUC CORPORATION

● Overseas Affiliated Companies

FANUC America Corporation

FANUC Europe Corporation, S.A.

BEIJING-FANUC Mechatronics CO., LTD

KOREA FANUC CORPORATION

TAIWAN FANUC CORPORATION

FANUC INDIA PRIVATE LIMITED

Phone: (+1)248-377-7000

Phone: (+352)727777-1

Phone: (+86)10-6298-4726

Phone: (+82)55-278-1200

Phone: (+886)4-2359-0522

Phone: (+91)80-2852-0057

● Headquarters 3580, Shibokusa, Oshino-mura,
Minamitsuru-gun Yamanashi, 401-0597, JAPAN
Phone: (+81)555-84-5555 <https://www.fanuc.co.jp/>

<https://www.fanucamerica.com/>

<https://www.fanuc.eu/>

<http://www.bj-fanuc.com.cn/>

<https://www.fkc.co.kr/>

<https://www.fanuctaiwan.com.tw/>

<https://www.fanucindia.com/>

• All specifications are subject to change without notice.
• No part of this catalog may be reproduced in any form.
• The products in the FANUC Series 0i-MODEL F Plus listed in this catalog are not subject to Items 2 to 15 in the Attachment to the Foreign Exchange Order of the “Foreign Exchange and Foreign Trade Law” but are subject to Item 16 (catch-all controls).
The export from Japan may be subject to an export license by the government of Japan.
Further, re-export to another country may be subject to the license of the government of the country from where the product is re-exported. Furthermore, the product may also be controlled by re-export regulations of the United States government.
Should you wish to export or re-export these products, please contact FANUC for advice.